Downloaded from: justpaste.it/159ca

[2.689]
X.Org X Server 1.16.4
Release Date: 2014-12-20
[2.689] X Protocol Version 11, Revision 0
[2.689] Build Operating System: Linux 3.16.0-4-amd64 x86_64 Debian
[2.689] Current Operating System: Linux PcSiva 3.16.0-4-amd64 #1 SMP Debian 3.16.39-1+deb8u2 (2017-03-07) x86_64
[2.689] Kernel command line: BOOT_IMAGE=/boot/vmlinuz-3.16.0-4-amd64 root=UUID=7d8a13f0-ae6d-4994-b970-1007724e01cd ro quiet
[2.689] Build Date: 11 February 2015 12:32:02AM
[2.689] xorg-server 2:1.16.4-1 (http://www.debian.org/support)
[2.689] Current version of pixman: 0.32.6
[2.689] Before reporting problems, check http://wiki.x.org
to make sure that you have the latest version.
[2.689] Markers: (--) probed, (**) from config file, (==) default setting,
(++) from command line, (!!) notice, (II) informational,
(WW) warning, (EE) error, (NI) not implemented, (??) unknown.
[2.689] (==) Log file: "/var/log/Xorg.0.log", Time: Fri Apr 7 01:53:24 2017
[2.693] (==) Using system config directory "/usr/share/X11/xorg.conf.d"
[2.694] (==) No Layout section. Using the first Screen section.
[2.694] (==) No screen section available. Using defaults.
[2.694] (**) |-->Screen "Default Screen Section" (0)
[2.694] (**) | |-->Monitor "<default monitor>"
[2.695] (==) No monitor specified for screen "Default Screen Section".
Using a default monitor configuration.
[2.695] (==) Automatically adding devices
[2.695] (==) Automatically enabling devices
[2.695] (==) Automatically adding GPU devices
[2.699] (WW) The directory "/usr/share/fonts/X11/cyrillic" does not exist.
[2.699] Entry deleted from font path.
[2.702] (==) FontPath set to:
/usr/share/fonts/X11/misc,
/usr/share/fonts/X11/100dpi/:unscaled,
/usr/share/fonts/X11/75dpi/:unscaled,
/usr/share/fonts/X11/Type1,
/usr/share/fonts/X11/100dpi,

```
    /usr/share/fonts/X11/75dpi,
    built-ins
[     2.702] (==) ModulePath set to "/usr/lib/xorg/modules"
[     2.702] (II) The server relies on udev to provide the list of input devices.
    If no devices become available, reconfigure udev or disable AutoAddDevices.
[     2.703] (II) Loader magic: 0x7f9085bc4d80
[     2.703] (II) Module ABI versions:
[     2.703]     X.Org ANSI C Emulation: 0.4
[     2.703]     X.Org Video Driver: 18.0
[     2.703]     X.Org XInput driver : 21.0
[     2.703]     X.Org Server Extension : 8.0
[     2.704] (--) PCI:*(0:0:2:0) 8086:1912:1043:8694 rev 6, Mem @ 0xd0000000/16777216,
0xc0000000/268435456, I/O @ 0x0000f000/64
[     2.705] (II) LoadModule: "glx"
[     2.705] (II) Loading /usr/lib/xorg/modules/extensions/libglx.so
[     2.718] (II) Module glx: vendor="X.Org Foundation"
[     2.718]     compiled for 1.16.4, module version = 1.0.0
[     2.718]     ABI class: X.Org Server Extension, version 8.0
[     2.718] (==) AIGLX enabled
[     2.718] (==) Matched intel as autoconfigured driver 0
[     2.718] (==) Matched modesetting as autoconfigured driver 1
[     2.718] (==) Matched fbdev as autoconfigured driver 2
[     2.718] (==) Matched vesa as autoconfigured driver 3
[     2.718] (==) Assigned the driver to the xf86ConfigLayout
[     2.718] (II) LoadModule: "intel"
[     2.718] (II) Loading /usr/lib/xorg/modules/drivers/intel_drv.so
[     2.726] (II) Module intel: vendor="X.Org Foundation"
[     2.726]     compiled for 1.15.99.904, module version = 2.21.15
[     2.726]     Module class: X.Org Video Driver
[     2.726]     ABI class: X.Org Video Driver, version 18.0
[     2.726] (II) LoadModule: "modesetting"
[     2.726] (II) Loading /usr/lib/xorg/modules/drivers/modesetting_drv.so
[     2.727] (II) Module modesetting: vendor="X.Org Foundation"
[     2.727]     compiled for 1.16.4, module version = 0.9.0
[     2.727]     Module class: X.Org Video Driver
[     2.727]     ABI class: X.Org Video Driver, version 18.0
[     2.727] (II) LoadModule: "fbdev"
[     2.727] (II) Loading /usr/lib/xorg/modules/drivers/fbdev_drv.so
[     2.728] (II) Module fbdev: vendor="X.Org Foundation"
```

```
[    2.728]    compiled for 1.15.99.904, module version = 0.4.4
[    2.728]    Module class: X.Org Video Driver
[    2.728]    ABI class: X.Org Video Driver, version 18.0
[    2.728] (II) LoadModule: "vesa"
[    2.728] (II) Loading /usr/lib/xorg/modules/drivers/vesa_drv.so
[    2.729] (II) Module vesa: vendor="X.Org Foundation"
[    2.729]    compiled for 1.15.99.904, module version = 2.3.3
[    2.729]    Module class: X.Org Video Driver
[    2.729]    ABI class: X.Org Video Driver, version 18.0
[    2.729] (II) intel: Driver for Intel(R) Integrated Graphics Chipsets:
   i810, i810-dc100, i810e, i815, i830M, 845G, 854, 852GM/855GM, 865G,
   915G, E7221 (i915), 915GM, 945G, 945GM, 945GME, Pineview GM,
   Pineview G, 965G, G35, 965Q, 946GZ, 965GM, 965GME/GLE, G33, Q35, Q33,
   GM45, 4 Series, G45/G43, Q45/Q43, G41, B43, HD Graphics,
   HD Graphics 2000, HD Graphics 3000, HD Graphics 2500,
   HD Graphics 4000, HD Graphics P4000, HD Graphics 4600,
   HD Graphics 5000, HD Graphics P4600/P4700, Iris(TM) Graphics 5100,
   HD Graphics 4400, HD Graphics 4200, Iris(TM) Pro Graphics 5200
[    2.730] (II) modesetting: Driver for Modesetting Kernel Drivers: kms
[    2.730] (II) FBDEV: driver for framebuffer: fbdev
[    2.730] (II) VESA: driver for VESA chipsets: vesa
[    2.730] (++) using VT number 7

[    2.751] (EE) open /dev/dri/card0: No such file or directory
[    2.751] (WW) Falling back to old probe method for modesetting
[    2.751] (EE) open /dev/dri/card0: No such file or directory
[    2.751] (II) Loading sub module "fbdevhw"
[    2.751] (II) LoadModule: "fbdevhw"
[    2.752] (II) Loading /usr/lib/xorg/modules/libfbdevhw.so
[    2.753] (II) Module fbdevhw: vendor="X.Org Foundation"
[    2.753]    compiled for 1.16.4, module version = 0.0.2
[    2.753]    ABI class: X.Org Video Driver, version 18.0
[    2.753] (**) FBDEV(1): claimed PCI slot 0@0:2:0
[    2.753] (II) FBDEV(1): using default device
[    2.753] (WW) Falling back to old probe method for vesa
[    2.753] (EE) Screen 0 deleted because of no matching config section.
[    2.753] (II) UnloadModule: "modesetting"
[    2.753] (II) FBDEV(0): Creating default Display subsection in Screen section
   "Default Screen Section" for depth/fbbpp 24/32
```

[2.753] (==) FBDEV(0): Depth 24, (==) framebuffer bpp 32
[2.753] (==) FBDEV(0): RGB weight 888
[2.753] (==) FBDEV(0): Default visual is TrueColor
[2.753] (==) FBDEV(0): Using gamma correction (1.0, 1.0, 1.0)
[2.753] (II) FBDEV(0): hardware: EFI VGA (video memory: 3072kB)
[2.753] (II) FBDEV(0): checking modes against framebuffer device...
[2.753] (II) FBDEV(0): checking modes against monitor...
[2.753] (--) FBDEV(0): Virtual size is 1024x768 (pitch 1024)
[2.753] (**) FBDEV(0): Built-in mode "current": 78.7 MHz, 59.9 kHz, 75.7 Hz
[2.753] (II) FBDEV(0): Modeline "current"x0.0 78.65 1024 1056 1184 1312 768 772 776 792 -hsync -vsync -csync (59.9 kHz b)
[2.753] (==) FBDEV(0): DPI set to (96, 96)
[2.753] (II) Loading sub module "fb"
[2.753] (II) LoadModule: "fb"
[2.753] (II) Loading /usr/lib/xorg/modules/libfb.so
[2.754] (II) Module fb: vendor="X.Org Foundation"
[2.754] compiled for 1.16.4, module version = 1.0.0
[2.755] ABI class: X.Org ANSI C Emulation, version 0.4
[2.755] (**) FBDEV(0): using shadow framebuffer
[2.755] (II) Loading sub module "shadow"
[2.755] (II) LoadModule: "shadow"
[2.755] (II) Loading /usr/lib/xorg/modules/libshadow.so
[2.755] (II) Module shadow: vendor="X.Org Foundation"
[2.755] compiled for 1.16.4, module version = 1.1.0
[2.755] ABI class: X.Org ANSI C Emulation, version 0.4
[2.755] (II) UnloadModule: "vesa"
[2.755] (II) Unloading vesa
[2.755] (==) Depth 24 pixmap format is 32 bpp
[2.755] (EE) FBDEV(0): FBIOBLANK: Invalid argument
[2.758] (==) FBDEV(0): Backing store enabled
[2.759] (==) FBDEV(0): DPMS enabled
[2.759] (==) RandR enabled
[2.764] (II) SELinux: Disabled on system
[2.764] (II) AIGLX: Screen 0 is not DRI2 capable
[2.764] (EE) AIGLX: reverting to software rendering
[2.845] (II) AIGLX: Loaded and initialized swrast
[2.845] (II) GLX: Initialized DRISWRAST GL provider for screen 0
[2.881] (II) config/udev: Adding input device Power Button (/dev/input/event6)
[2.881] (**) Power Button: Applying InputClass "evdev keyboard catchall"

[2.881] (II) LoadModule: "evdev"
[2.881] (II) Loading /usr/lib/xorg/modules/input/evdev_drv.so
[2.883] (II) Module evdev: vendor="X.Org Foundation"
[2.883] compiled for 1.16.0, module version = 2.9.0
[2.883] Module class: X.Org XInput Driver
[2.883] ABI class: X.Org XInput driver, version 21.0
[2.883] (II) Using input driver 'evdev' for 'Power Button'
[2.883] (**) Power Button: always reports core events
[2.883] (**) evdev: Power Button: Device: "/dev/input/event6"
[2.883] (--) evdev: Power Button: Vendor 0 Product 0x1
[2.883] (--) evdev: Power Button: Found keys
[2.883] (II) evdev: Power Button: Configuring as keyboard
[2.883] (**) Option "config_info"
"udev:/sys/devices/LNXSYSTM:00/LNXPWRBN:00/input/input9/event6"
[2.883] (II) XINPUT: Adding extended input device "Power Button" (type: KEYBOARD, id 6)
[2.883] (**) Option "xkb_rules" "evdev"
[2.883] (**) Option "xkb_model" "pc105"
[2.883] (**) Option "xkb_layout" "fr"
[2.883] (**) Option "xkb_variant" "latin9"
[2.893] (II) config/udev: Adding input device Power Button (/dev/input/event5)
[2.893] (**) Power Button: Applying InputClass "evdev keyboard catchall"
[2.893] (II) Using input driver 'evdev' for 'Power Button'
[2.893] (**) Power Button: always reports core events
[2.893] (**) evdev: Power Button: Device: "/dev/input/event5"
[2.893] (--) evdev: Power Button: Vendor 0 Product 0x1
[2.893] (--) evdev: Power Button: Found keys
[2.893] (II) evdev: Power Button: Configuring as keyboard
[2.893] (**) Option "config_info"
"udev:/sys/devices/LNXSYSTM:00/LNXSYBUS:00/PNP0C0C:00/input/input8/event5"
[2.893] (II) XINPUT: Adding extended input device "Power Button" (type: KEYBOARD, id 7)
[2.893] (**) Option "xkb_rules" "evdev"
[2.893] (**) Option "xkb_model" "pc105"
[2.893] (**) Option "xkb_layout" "fr"
[2.893] (**) Option "xkb_variant" "latin9"
[2.893] (II) config/udev: Adding input device Sleep Button (/dev/input/event4)
[2.893] (**) Sleep Button: Applying InputClass "evdev keyboard catchall"
[2.893] (II) Using input driver 'evdev' for 'Sleep Button'
[2.893] (**) Sleep Button: always reports core events
[2.893] (**) evdev: Sleep Button: Device: "/dev/input/event4"

[2.893] (--) evdev: Sleep Button: Vendor 0 Product 0x3
[2.893] (--) evdev: Sleep Button: Found keys
[2.893] (II) evdev: Sleep Button: Configuring as keyboard
[2.893] (**) Option "config_info" "udev:/sys/devices/LNXSYSTM:00/LNXSYBUS:00/PNP0C0E:00/input/input7/event4"
[2.893] (II) XINPUT: Adding extended input device "Sleep Button" (type: KEYBOARD, id 8)
[2.893] (**) Option "xkb_rules" "evdev"
[2.893] (**) Option "xkb_model" "pc105"
[2.893] (**) Option "xkb_layout" "fr"
[2.893] (**) Option "xkb_variant" "latin9"
[2.893] (II) config/udev: Adding input device MOSART Semi. 2.4G Keyboard Mouse (/dev/input/event2)
[2.893] (**) MOSART Semi. 2.4G Keyboard Mouse: Applying InputClass "evdev keyboard catchall"
[2.893] (II) Using input driver 'evdev' for 'MOSART Semi. 2.4G Keyboard Mouse'
[2.893] (**) MOSART Semi. 2.4G Keyboard Mouse: always reports core events
[2.893] (**) evdev: MOSART Semi. 2.4G Keyboard Mouse: Device: "/dev/input/event2"
[2.893] (--) evdev: MOSART Semi. 2.4G Keyboard Mouse: Vendor 0x62a Product 0x4101
[2.893] (--) evdev: MOSART Semi. 2.4G Keyboard Mouse: Found keys
[2.893] (II) evdev: MOSART Semi. 2.4G Keyboard Mouse: Configuring as keyboard
[2.893] (**) Option "config_info" "udev:/sys/devices/pci0000:00/0000:00:14.0/usb1/1-10/1-10:1.0/0003:062A:4101.0003/input/input5/event2"
[2.893] (II) XINPUT: Adding extended input device "MOSART Semi. 2.4G Keyboard Mouse" (type: KEYBOARD, id 9)
[2.893] (**) Option "xkb_rules" "evdev"
[2.893] (**) Option "xkb_model" "pc105"
[2.893] (**) Option "xkb_layout" "fr"
[2.893] (**) Option "xkb_variant" "latin9"
[2.894] (II) config/udev: Adding input device MOSART Semi. 2.4G Keyboard Mouse (/dev/input/event3)
[2.894] (**) MOSART Semi. 2.4G Keyboard Mouse: Applying InputClass "evdev pointer catchall"
[2.894] (**) MOSART Semi. 2.4G Keyboard Mouse: Applying InputClass "evdev keyboard catchall"
[2.894] (II) Using input driver 'evdev' for 'MOSART Semi. 2.4G Keyboard Mouse'
[2.894] (**) MOSART Semi. 2.4G Keyboard Mouse: always reports core events
[2.894] (**) evdev: MOSART Semi. 2.4G Keyboard Mouse: Device: "/dev/input/event3"
[2.894] (--) evdev: MOSART Semi. 2.4G Keyboard Mouse: Vendor 0x62a Product 0x4101
[2.894] (--) evdev: MOSART Semi. 2.4G Keyboard Mouse: Found 9 mouse buttons

[2.894] (--) evdev: MOSART Semi. 2.4G Keyboard Mouse: Found scroll wheel(s)
[2.894] (--) evdev: MOSART Semi. 2.4G Keyboard Mouse: Found relative axes
[2.894] (--) evdev: MOSART Semi. 2.4G Keyboard Mouse: Found x and y relative axes
[2.894] (--) evdev: MOSART Semi. 2.4G Keyboard Mouse: Found absolute axes
[2.894] (II) evdev: MOSART Semi. 2.4G Keyboard Mouse: Forcing absolute x/y axes to exist.
[2.894] (--) evdev: MOSART Semi. 2.4G Keyboard Mouse: Found keys
[2.894] (II) evdev: MOSART Semi. 2.4G Keyboard Mouse: Configuring as mouse
[2.894] (II) evdev: MOSART Semi. 2.4G Keyboard Mouse: Configuring as keyboard
[2.894] (II) evdev: MOSART Semi. 2.4G Keyboard Mouse: Adding scrollwheel support
[2.894] (**) evdev: MOSART Semi. 2.4G Keyboard Mouse: YAxisMapping: buttons 4 and 5
[2.894] (**) evdev: MOSART Semi. 2.4G Keyboard Mouse: EmulateWheelButton: 4, EmulateWheelInertia: 10, EmulateWheelTimeout: 200
[2.894] (**) Option "config_info" "udev:/sys/devices/pci0000:00/0000:00:14.0/usb1/1-10/1-10:1.1/0003:062A:4101.0004/input/input6/event3"
[2.894] (II) XINPUT: Adding extended input device "MOSART Semi. 2.4G Keyboard Mouse" (type: KEYBOARD, id 10)
[2.894] (**) Option "xkb_rules" "evdev"
[2.894] (**) Option "xkb_model" "pc105"
[2.894] (**) Option "xkb_layout" "fr"
[2.894] (**) Option "xkb_variant" "latin9"
[2.894] (II) evdev: MOSART Semi. 2.4G Keyboard Mouse: initialized for relative axes.
[2.894] (WW) evdev: MOSART Semi. 2.4G Keyboard Mouse: ignoring absolute axes.
[2.894] (**) MOSART Semi. 2.4G Keyboard Mouse: (accel) keeping acceleration scheme 1
[2.894] (**) MOSART Semi. 2.4G Keyboard Mouse: (accel) acceleration profile 0
[2.894] (**) MOSART Semi. 2.4G Keyboard Mouse: (accel) acceleration factor: 2.000
[2.894] (**) MOSART Semi. 2.4G Keyboard Mouse: (accel) acceleration threshold: 4
[2.894] (II) config/udev: Adding input device MOSART Semi. 2.4G Keyboard Mouse (/dev/input/mouse0)
[2.894] (II) No input driver specified, ignoring this device.
[2.894] (II) This device may have been added with another device file.
[2.894] (II) config/udev: Adding input device Logitech Logitech Illuminated Keyboard (/dev/input/event0)
[2.894] (**) Logitech Logitech Illuminated Keyboard: Applying InputClass "evdev keyboard catchall"
[2.894] (II) Using input driver 'evdev' for 'Logitech Logitech Illuminated Keyboard'
[2.894] (**) Logitech Logitech Illuminated Keyboard: always reports core events
[2.894] (**) evdev: Logitech Logitech Illuminated Keyboard: Device: "/dev/input/event0"
[2.894] (--) evdev: Logitech Logitech Illuminated Keyboard: Vendor 0x46d Product 0xc318

[2.894] (--) evdev: Logitech Logitech Illuminated Keyboard: Found keys
[2.894] (II) evdev: Logitech Logitech Illuminated Keyboard: Configuring as keyboard
[2.894] (**) Option "config_info" "udev:/sys/devices/pci0000:00/0000:00:14.0/usb1/1-9/1-9:1.0/0003:046D:C318.0001/input/input3/event0"
[2.894] (II) XINPUT: Adding extended input device "Logitech Logitech Illuminated Keyboard" (type: KEYBOARD, id 11)
[2.894] (**) Option "xkb_rules" "evdev"
[2.894] (**) Option "xkb_model" "pc105"
[2.894] (**) Option "xkb_layout" "fr"
[2.894] (**) Option "xkb_variant" "latin9"
[2.894] (II) config/udev: Adding input device Logitech Logitech Illuminated Keyboard (/dev/input/event1)
[2.894] (**) Logitech Logitech Illuminated Keyboard: Applying InputClass "evdev keyboard catchall"
[2.894] (II) Using input driver 'evdev' for 'Logitech Logitech Illuminated Keyboard'
[2.894] (**) Logitech Logitech Illuminated Keyboard: always reports core events
[2.894] (**) evdev: Logitech Logitech Illuminated Keyboard: Device: "/dev/input/event1"
[2.895] (--) evdev: Logitech Logitech Illuminated Keyboard: Vendor 0x46d Product 0xc318
[2.895] (--) evdev: Logitech Logitech Illuminated Keyboard: Found 1 mouse buttons
[2.895] (--) evdev: Logitech Logitech Illuminated Keyboard: Found scroll wheel(s)
[2.895] (--) evdev: Logitech Logitech Illuminated Keyboard: Found relative axes
[2.895] (II) evdev: Logitech Logitech Illuminated Keyboard: Forcing relative x/y axes to exist.
[2.895] (--) evdev: Logitech Logitech Illuminated Keyboard: Found absolute axes
[2.895] (II) evdev: Logitech Logitech Illuminated Keyboard: Forcing absolute x/y axes to exist.
[2.895] (--) evdev: Logitech Logitech Illuminated Keyboard: Found keys
[2.895] (II) evdev: Logitech Logitech Illuminated Keyboard: Configuring as mouse
[2.895] (II) evdev: Logitech Logitech Illuminated Keyboard: Configuring as keyboard
[2.895] (II) evdev: Logitech Logitech Illuminated Keyboard: Adding scrollwheel support
[2.895] (**) evdev: Logitech Logitech Illuminated Keyboard: YAxisMapping: buttons 4 and 5
[2.895] (**) evdev: Logitech Logitech Illuminated Keyboard: EmulateWheelButton: 4, EmulateWheelInertia: 10, EmulateWheelTimeout: 200
[2.895] (**) Option "config_info" "udev:/sys/devices/pci0000:00/0000:00:14.0/usb1/1-9/1-9:1.1/0003:046D:C318.0002/input/input4/event1"
[2.895] (II) XINPUT: Adding extended input device "Logitech Logitech Illuminated Keyboard" (type: KEYBOARD, id 12)
[2.895] (**) Option "xkb_rules" "evdev"
[2.895] (**) Option "xkb_model" "pc105"

[2.895] (**) Option "xkb_layout" "fr"
[2.895] (**) Option "xkb_variant" "latin9"
[2.895] (II) evdev: Logitech Logitech Illuminated Keyboard: initialized for relative axes.
[2.895] (WW) evdev: Logitech Logitech Illuminated Keyboard: ignoring absolute axes.
[2.895] (**) Logitech Logitech Illuminated Keyboard: (accel) keeping acceleration scheme 1
[2.895] (**) Logitech Logitech Illuminated Keyboard: (accel) acceleration profile 0
[2.895] (**) Logitech Logitech Illuminated Keyboard: (accel) acceleration factor: 2.000
[2.895] (**) Logitech Logitech Illuminated Keyboard: (accel) acceleration threshold: 4
[2.895] (II) config/udev: Adding input device Eee PC WMI hotkeys (/dev/input/event8)
[2.895] (**) Eee PC WMI hotkeys: Applying InputClass "evdev keyboard catchall"
[2.895] (II) Using input driver 'evdev' for 'Eee PC WMI hotkeys'
[2.895] (**) Eee PC WMI hotkeys: always reports core events
[2.895] (**) evdev: Eee PC WMI hotkeys: Device: "/dev/input/event8"
[2.895] (--) evdev: Eee PC WMI hotkeys: Vendor 0 Product 0
[2.895] (--) evdev: Eee PC WMI hotkeys: Found keys
[2.895] (II) evdev: Eee PC WMI hotkeys: Configuring as keyboard
[2.895] (**) Option "config_info" "udev:/sys/devices/platform/eeepc-wmi/input/input11/event8"
[2.895] (II) XINPUT: Adding extended input device "Eee PC WMI hotkeys" (type: KEYBOARD, id 13)
[2.895] (**) Option "xkb_rules" "evdev"
[2.895] (**) Option "xkb_model" "pc105"
[2.895] (**) Option "xkb_layout" "fr"
[2.895] (**) Option "xkb_variant" "latin9"
[2.895] (II) config/udev: Adding input device PC Speaker (/dev/input/event7)
[2.895] (II) No input driver specified, ignoring this device.
[2.895] (II) This device may have been added with another device file.
[2.896] (EE) FBDEV(0): FBIOBLANK: Invalid argument
[3.285] (II) config/udev: Adding input device HDA Intel PCH Front Mic (/dev/input/event9)
[3.286] (II) No input driver specified, ignoring this device.
[3.286] (II) This device may have been added with another device file.
[3.286] (II) config/udev: Adding input device HDA Intel PCH Line (/dev/input/event11)
[3.286] (II) No input driver specified, ignoring this device.
[3.286] (II) This device may have been added with another device file.
[3.286] (II) config/udev: Adding input device HDA Intel PCH Rear Mic (/dev/input/event10)
[3.286] (II) No input driver specified, ignoring this device.
[3.286] (II) This device may have been added with another device file.
[3.287] (II) config/udev: Adding input device HDA Intel PCH Front Headphone (/dev/input/event13)

[3.287] (II) No input driver specified, ignoring this device.
[3.287] (II) This device may have been added with another device file.
[3.287] (II) config/udev: Adding input device HDA Intel PCH HDMI/DP,pcm=3 (/dev/input/event14)
[3.287] (II) No input driver specified, ignoring this device.
[3.287] (II) This device may have been added with another device file.
[3.287] (II) config/udev: Adding input device HDA Intel PCH Line Out (/dev/input/event12)
[3.287] (II) No input driver specified, ignoring this device.
[3.287] (II) This device may have been added with another device file.
[5.037] (EE) FBDEV(0): FBIOBLANK: Invalid argument
[13.282] (EE) FBDEV(0): FBIOBLANK: Invalid argument