

## DebugLog

Running - OS: <strong>Windows</strong>, Chrome: <strong>77.0.3865.120</strong>,

Configurator: <strong>1.2.0</strong>

Last used port wasn't saved "yet", auto-select disabled.

PortHandler - Found: COM9

Connecting to: COM9

SERIAL: Connection opened with ID: 1, Baud: 115200

Serial port <span style="color: green">successfully</span> opened with ID: 1

MultiWii API version <span style="color: green">received</span> - <strong>1.43.0</strong>

Flight controller info, identifier: <strong>BTFL</strong>, version: <strong>4.2.5</strong>

Running firmware released on: <strong>Nov 22 2020 18:38:23</strong>

Board: <strong>S405</strong>, version: <strong>0</strong>

Unique device ID <span style="color: green">received</span> -

<strong>0x4d00523436510c30333337</strong>

sending cmd InterfaceExit 0 0

received cmd\_InterfaceExit ACK\_OK 0 0

SERIAL: Connection with ID: 1 closed, Sent: 186 bytes, Received: 329 bytes

Connecting to: COM9

SERIAL: Connection opened with ID: 2, Baud: 115200

Serial port <span style="color: green">successfully</span> opened with ID: 2

MultiWii API version <span style="color: green">received</span> - <strong>1.43.0</strong>

Flight controller info, identifier: <strong>BTFL</strong>, version: <strong>4.2.5</strong>

Running firmware released on: <strong>Nov 22 2020 18:38:23</strong>

Board: <strong>S405</strong>, version: <strong>0</strong>

Unique device ID <span style="color: green">received</span> -

<strong>0x4d00523436510c30333337</strong>

Reading setup

sending cmd\_DeviceInitFlash 0 0

received cmd DeviceInitFlash ACK OK 0 178,232,100,1

sending cmd\_DeviceRead 1a00 112

received cmd DeviceRead ACK OK 1a00

```
32,32,32,32,32,32
sending cmd DeviceReset 0 0
received cmd DeviceReset ACK OK 0 0
sending cmd DeviceInitFlash 0 1
received cmd_DeviceInitFlash ACK_D_GENERAL_ERROR 0 0,0,100,1
received cmd DeviceInitFlash ACK D GENERAL ERROR 0 0,0,100,1
ESC 2 read settings failed cmd DeviceInitFlash ACK D GENERAL ERROR
sending cmd DeviceInitFlash 0 2
received cmd DeviceInitFlash ACK_OK 0 178,232,100,1
sending cmd DeviceRead 1a00 112
received cmd DeviceRead ACK OK 1a00
16,79,33,255,255,255,255,255,255,7,255,2,255,85,170,1,255,255,255,255,255,4,255,255,255
32,32,32,32,32,32
sending cmd DeviceReset 0 2
received cmd DeviceReset ACK OK 0 0
sending cmd DeviceInitFlash 0 3
received cmd DeviceInitFlash ACK OK 0 178,232,100,1
sending cmd DeviceRead 1a00 112
received cmd DeviceRead ACK OK 1a00
16,79,33,255,255,255,255,255,255,7,255,1,255,85,170,1,255,255,255,255,255,4,255,255,255
32,32,32,32,32,32
sending cmd_DeviceReset 0 3
received cmd DeviceReset ACK OK 0 0
Reading setup <span style="color: green">finished</span>
Reading setup
sending cmd DeviceInitFlash 0 0
received cmd_DeviceInitFlash ACK_OK 0 178,232,100,1
sending cmd DeviceRead 1a00 112
received cmd DeviceRead ACK OK 1a00
16,79,33,255,255,255,255,255,255,7,255,1,255,85,170,1,255,255,255,255,255,4,255,255,255
```

sending cmd\_DeviceReset 0 0

received cmd DeviceReset ACK OK 0 0

sending cmd DeviceInitFlash 0 1

received cmd\_DeviceInitFlash ACK\_D\_GENERAL\_ERROR 0 0,0,100,1

received cmd DeviceInitFlash ACK D GENERAL ERROR 0 0,0,100,1

ESC 2 read settings failed cmd DeviceInitFlash ACK D GENERAL ERROR

sending cmd\_DeviceInitFlash 0 2

received cmd\_DeviceInitFlash ACK\_OK 0 178,232,100,1

sending cmd DeviceRead 1a00 112

received cmd DeviceRead ACK OK 1a00

32,32,32,32,32,32

sending cmd DeviceReset 0 2

received cmd\_DeviceReset ACK\_OK 0 0

sending cmd DeviceInitFlash 0 3

received cmd\_DeviceInitFlash ACK\_OK 0 178,232,100,1

sending cmd DeviceRead 1a00 112

received cmd DeviceRead ACK OK 1a00

16,79,33,255,255,255,255,255,255,7,255,1,255,85,170,1,255,255,255,255,255,4,255,255,255

32,32,32,32,32,32

sending cmd DeviceReset 0 3

received cmd DeviceReset ACK OK 0 0

Reading setup <span style="color: green">finished</span>