



```
/**
 * Application entry point
 *
 * Example - run a particular store or website:
 * -----
 * require __DIR__ . '/app/bootstrap.php';
 * $params = $_SERVER;
 * $params[\Magento\Store\Model\StoreManager::PARAM_RUN_CODE] = 'website2';
 * $params[\Magento\Store\Model\StoreManager::PARAM_RUN_TYPE] = 'website';
 * $bootstrap = \Magento\Framework\App\Bootstrap::create(BP, $params);
 * V** @var \Magento\Framework\App\Http $app */
 * $app = $bootstrap->createApplication(\Magento\Framework\App\Http::class);
 * $bootstrap->run($app);
 * -----
 *
 * Copyright © Magento, Inc. All rights reserved.
 * See COPYING.txt for license details.
 */
try {
// require __DIR__ . '/app/bootstrap.php';
require __DIR__ . '/../app/bootstrap.php';
} catch (\Exception $e) {
echo <<<HTML
```

Autoload error

```
{ $e->getMessage() }
```

```
HTML;
```

```
exit(1);
```

```
}
```

```
// $bootstrap = \Magento\Framework\App\Bootstrap::create(BP, $_SERVER);
```

```
/** @var \Magento\Framework\App\Http $app */
```

```
// $app = $bootstrap->createApplication(\Magento\Framework\App\Http::class);
```

```
// $bootstrap->run($app);  
$params = $_SERVER;  
$params[\Magento\Store\Model\StoreManager::PARAM_RUN_CODE] = 'usa_website';  
//Website code as same in admin panel  
$params[\Magento\Store\Model\StoreManager::PARAM_RUN_TYPE] = 'website';  
$bootstrap = \Magento\Framework\App\Bootstrap::create(BP, $params);  
/** @var \Magento\Framework\App\Http $app */  
$app = $bootstrap->createApplication('Magento\Framework\App\Http');  
$bootstrap->run($app);
```