

Screws Small Encyclopedia

Sometimes You do not know, what screw you need to turn this piece of furniture. That is why this little encyclopedia was created.

Screws





Wood Screws

Screws with a smooth shank and tapered point for use in wood, Abbreviated WS



Self Drilling SMS

A sheet metal screw with a self drilling point.




Machine Screws

Screws with threads for use with a nut or tapped hole. Abbreviated MS



Thread Cutting Machine Screws

Machine screws with a thread cutting (self tapping) point.



Sheet Metal Screws

Fully threaded screws with a point for use in sheet metal. Abbreviated SMS





Hex Bolts

Bolts with a hexagonal head with threads for use with a nut or tapped hole. Abbreviated HHMB or HXBT.



Carriage Bolts

Bolts with a smooth rounded head that has a small square section underneath.



Lag Bolts

Bolts with a wood thread and pointed tip. Abbreviated Lag.



Socket Screws

Socket screws, also known as Allen Head, are fastened with a hex Allen wrench.



Set Screws

Machine screws with no head for screwing all the way into threaded holes.



Eye Bolts

A bolt with a circular ring on the head end. Used for attaching a rope or chain.



Eye Lags

Similar to an eye bolt but with wood threads instead of machine thread.



J-Bolts

J shaped bolts are used for tie-downs or as an open eye bolt.



U-Bolts

Bolts in U shape for attaching to pipe or other round surfaces. Also available with a square bend.



Shoulder Bolts

Shoulder bolts (also known as stripper bolts) are used to create a pivot point.



Elevator Bolts

Elevator bolts are often used in conveyor systems. They have a large, flat head.



Sex Bolts

Sex bolts (a.k.a. barrel nuts or Chicago bolts) have a female thread and are used for through bolting applications where a head is desired on both sides of the joint.



Mating Screws

Mating screws have a shoulder that matches the diameter of the sex bolts they are used with.



Hanger Bolts

Hanger bolts have wood thread on one end and machine thread on the other end



A countersunk head with a flat top. Abbreviated FH





Round

A domed head. Abbreviated RH





A countersunk head with a

rounded top.

Abbreviated OH or OV

A hexagonal head Abbreviated HH or HX



A low-profile rounded head using a socket drive.



A slightly rounded head with short vertical sides. Abbreviated PN



An extra wide head with a rounded top.



Hex Washer

A hex head with built in washer.





Slotted Hex Washer

A hex head with built in washer and a slot.





Socket Cap

A small cylindrical head using a socket drive.

Drive Types





Phillips and Frearson

An X-shaped drive. Abbreviated PH



One Way

Installs with a normal slotted driver but can not be removed without special tools.





Slotted

A slot in the head. Abbreviated SL





Square

Also known as Robertson drive. Abbreviated SQ or SD.





Combination

A combination of slotted and Phillips drives. Abbreviated combo





Torx

A six-pointed star pattern, specifically designed to prevent cam-out and stripped heads.





Socket, Hex or Allen

A hexagonal hole for use with an Allen wrench.

Washer Type



A flat washer, used to distribute load. Available in SAE, USS and other patterns.



Fender

An oversize flat washer used to further distribute load especially on soft materials.



Finishing

A washer used to obtain a 'finished' look. Usually used with oval head screws.

Square

A square shaped washer.



Split Lock

The most common style of washer used to prevent nuts and bolts from backing out.



Dock

Dock washers have a larger outside diameter and are thicker than standard.




External Tooth Lock

A washer with external 'teeth'. Used to prevent nuts and bolts from backing out.



Internal Tooth Lock

A washer with internal 'teeth'. Used to prevent nuts and bolts





Ogee

Thick, large diameter, cast iron washers with a curved or sculpted appearance. Typically used in dock and wood construction.

Nut Types



Hex
A six sided nut. Also referred to
as a Finished Hex Nut.



Heavy Hex
A heavier pattern version of a standard hex nut.



Nylon Insert Lock
A nut with a nylon insert to
prevent backing off. Also
referred to as a Nylock.



Jam
A hex nut with a reduced height.



Nylon Insert Jam Lock
A nylock nut with a reduced
height.



Wing
A nut with 'wings' for hand tightening.



Cap
A nut with a domed top over the end of the fastener.



Acorn
Acorn nuts are a high crown
type of cap nut, used for
appearance.



Flange
A nut with a built in washer like flange.



Tee
A nut designed to be driven into wood to create a threaded hole.



Square A four sided nut.




Prevailing Torque Lock
A non-reversible lock nut used
for high temperature applications.



K-Lock or Kep A nut with an attached free-spinning external tooth lock washer.



Coupling
Coupling nuts are long nuts
used to connect pieces of
threaded rod or other male
fasteners.



Slotted
Slotted nuts are used in conjunction with a cotter pin on drilled shank fasteners to prevent loosening.



Castle
Castle nuts are used in
conjunction with a cotter pin
on drilled shank fasteners to
prevent loosening.

by Boltdepot.com