



Hey so Ive got bind9 installed here are some config files:

/etc/bind/named.conf.local

```
zone "open-ims.test" {  
    type master;  
    file "pri/open-ims.dnszone";  
    notify no;  
};
```

/etc/bind/named.conf.options

```
options {  
    directory "/var/cache/bind";  
  
    // If there is a firewall between you and nameservers you want  
    // to talk to, you may need to fix the firewall to allow multiple  
    // ports to talk. See http://www.kb.cert.org/vuls/id/800113  
  
    // If your ISP provided one or more IP addresses for stable  
    // nameservers, you probably want to use them as forwarders.  
    // Uncomment the following block, and insert the addresses replacing  
    // the all-0's placeholder.  
  
    // forwarders {  
    // 0.0.0.0;  
    // };  
  
    auth-nxdomain no; # conform to RFC1035  
    listen-on-v6 { any; };  
};
```

/etc/bind/pri/open-ims.dnszone

\$ORIGIN open-ims.test.

\$TTL 1W

@ 1D IN SOA localhost. root.localhost. (

2006101001 ; serial

3H ; refresh

15M ; retry

1W ; expiry

1D) ; minimum

1D IN NS ns

ns 1D IN A 127.0.0.1

pcscf 1D IN A 127.0.0.1

_sip.pcscf 1D SRV 0 0 4060 pcscf

_sip._udp.pcscf 1D SRV 0 0 4060 pcscf

_sip._tcp.pcscf 1D SRV 0 0 4060 pcscf

icscf 1D IN A 127.0.0.1

_sip 1D SRV 0 0 5060 icscf

_sip._udp 1D SRV 0 0 5060 icscf

_sip._tcp 1D SRV 0 0 5060 icscf

open-ims.test. 1D IN A 127.0.0.1

open-ims.test. 1D IN NAPTR 10 50 "s" "SIP+D2U" "" _sip._udp

open-ims.test. 1D IN NAPTR 20 50 "s" "SIP+D2T" "" _sip._tcp

scscf 1D IN A 127.0.0.1

_sip.scscf 1D SRV 0 0 6060 scscf

_sip._udp.scscf 1D SRV 0 0 6060 scscf

_sip._tcp.scscf 1D SRV 0 0 6060 scscf

trcf 1D IN A 127.0.0.1

_sip.trcf 1D SRV 0 0 3060 trcf

_sip._udp.trcf 1D SRV 0 0 3060 trcf

_sip._tcp.trcf 1D SRV 0 0 3060 trcf

bgcf 1D IN A 127.0.0.1

_sip.bgcf 1D SRV 0 0 7060 bgcf

_sip._udp.bgcf 1D SRV 0 0 7060 bgcf

_sip._tcp.bgcf 1D SRV 0 0 7060 bgcf

mgcf 1D IN A 127.0.0.1

_sip.mgcf 1D SRV 0 0 8060 mgcf

_sip._udp.mgcf 1D SRV 0 0 8060 mgcf

_sip._tcp.mgcf 1D SRV 0 0 8060 mgcf

hss 1D IN A 127.0.0.1

ue 1D IN A 127.0.0.1

presence 1D IN A 127.0.0.1

pcrf 1D IN A 127.0.0.1

clf 1D IN A 127.0.0.1

/etc/resolv.conf

nameserver 127.0.0.1

domain open-ims.test

search open-ims.test

when I restart bind9 and try "dig @127.0.0.1 pcscf.open-ims.test" i get:

; <<>> DiG 9.7.2-P3 <<>> @127.0.0.1 pcscf.open-ims.test

; (1 server found)

;; global options: +cmd

;; Got answer:

```
;; ->>HEADER<- opcode: QUERY, status: SERVFAIL, id: 41317  
;; flags: qr rd ra; QUERY: 1, ANSWER: 0, AUTHORITY: 0, ADDITIONAL: 0
```

```
;; QUESTION SECTION:  
;pcscf.open-ims.test. IN A
```

```
;; Query time: 0 msec  
;; SERVER: 127.0.0.1#53(127.0.0.1)  
;; WHEN: Mon Mar 14 19:05:12 2011  
;; MSG SIZE rcvd: 37
```

why I dont get any answer?