



How To Use A Divot Tool: What Are Pitch Marks And 'Divots'?



Every player should have a divot instrument. The most crucial aspect to remember when making low scores is putting. A green with pitch marks on it can cause golfers to suffer.

Correctly fixing a pitch mark is a fast and simple procedure, which will ensure a fair playing surface for other golfers who are enjoying the course. Many golfers are surprised to discover that they did not employ the right method to repair their pitch marks, and can gain from understanding the correct technique.

The importance of repairing pitch Marks

A tool for repairing pitch marks is commonly referred to as a "divot repair" tool, or a "divot tool." If a golfer hits the green using their golf ball the impact leaves a tiny circular indentation on the green that is referred to as a "pitch" mark. If left unfixed the pitch marks could alter the surface of the putting area and make it difficult to putt.

Pitch marks are often called "divots" but technically speaking, they refer to holes in fairways or tee boxes that remain after the golf club hits the grass. The misinterpretation that is commonplace of the terms is a nagging problem for some golfers. But they're often used in conjunction.

If you take a closer look at the tools next time you go to a professional shop, you'll see that they're often referred to as "divot repair" or "pitch repair tool for marks." This is done to ensure that the putting surface is in good condition for the next round.

What can a divot tool be employed to do?

To repair any ball marks that golfers leave when they land on the green, the term is [golf divot tool](#). Similar to raking bunkers when you hit the green, repairing the marks left by your ball every time will ensure fair playing conditions for all golfers. The [golf divot tool](#) is a must-have accessory for every golf bag, must be included.

How Do I Use A Golf Divot Tool?

Finding the pitch mark itself is the initial step towards repairing it. It is possible to locate the pitch mark by making note of the location where the ball will land during approach shots and the direction it turns. Marks left by shorter irons and wedges will usually be more deep and more easily identifiable because of the greater trajectory of the ball's flight.

If you can't manage to locate your pitch mark, the best way to practice is to fix it if it is available. In reality, many charitable golfers have formed the habit of fixing an additional ball mark alongside their own.

After your ball mark is found, it's time to repair it. Beginning just to the outside of one edge of the mark, drive the pointed edge of the tool into ground and then push the turf inward towards the center. Repeat this motion around all sides of the mark while continuing to push the grass towards the center. What was once a hole in the green is now an uneven pile of mashed-up grass. Make sure to tap the mound with the putter's bottom, tapping until the surface is flat and playable.

Golfers frequently misuse their divot tool, which can lead to slower healing on the green. A common mistake made following the drive of the prongs into soil is pushing the tool inward instead of pushing it outward. Instead, lift the mark from below the mark.

Although this method flattens the pitch mark, it lifts dirt up to the surface instead of pulling the grass back together. The dirt that is exposed will require several weeks to grow back in while the proper method allows the grass to grow back into a clump and heal in less than one week in most instances.