

## Asme B18 2.1 Pdf

ASME B [Revision of ASME B (R)] Square, Hex, Heavy Hex, and Askew Head Bolts and Hex, Heavy Hex, Hex Flange, Lobed Head, and Lag Screws (Inch. Head Dimensions: ASME B specifies the dimensions of the hexagonal head, including head width across flats (measured between parallel sides of the hex head) and head height. Heavy hex structural bolts, formerly covered in ANSI B, are now covered in ASME B Additional head types (hex flange and lobed heads) and additional sizes commonly used (1 . Mar 5, · ASME B Square, Hex, Heavy Hex, and Askew Head Bolts and Hex, Heavy Hex, Hex Flange, Lobed Head, and Lag Screws (Inch. Series) The errata corrections listed below apply to ASME B These corrections will be incorporated into the next edition of B Page Location Change 15 Table 8 In Note (3), formula for "L G, max.". ASME B, Unified Inch Screw Threads (UN and UNR Thread Form) ASME B, Gages and Gaging for Unified Inch Screw Threads Terminology As used in this Standard, "short bolt" or "short screw" means a bolt or screw of a diameter-length combination 1 ASME B 2 ASME B, Screw Thread Gaging Systems for Acceptability: Inch and. Hex flange head and lobed head designs are new in this revision, as are screw sizes 1 5/8, 1 7/8, and 3 1/8 through 6 inches. Appendices covering gages and gaging information plus formulas on which dimensional data are based are included. Heavy hex structural bolts, formerly covered in ANSI B, are now covered in ASME B Table of.